

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATHESON TRI-GAS, INC.
959 ROUTE 46 EAST
PARSIPPANY, NEW JERSEY 07054-0624

EMERGENCY CONTACT:
CHEMTREC 1-800-424-9300
INFORMATION CONTACT:
973-257-1100

SUBSTANCE: PROPYLENE

TRADE NAMES/SYNONYMS:

MTG MSDS 77; PROPENE; METHYLETHENE; METHYLETHYLENE; 1-PROPYLENE; 1-PROPENE; UN 1077; C3H6; MAT19830; RTECS UC6740000

CHEMICAL FAMILY: hydrocarbons, aliphatic

CREATION DATE: Jan 24 1989

REVISION DATE: Dec 15 2003

2. COMPOSITION, INFORMATION ON INGREDIENTS


COMPONENT: PROPYLENE

CAS NUMBER: 115-07-1

PERCENTAGE: 100.0

3. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=1 FIRE=4 REACTIVITY=1



EMERGENCY OVERVIEW:

COLOR: colorless

PHYSICAL FORM: gas

MAJOR HEALTH HAZARDS: central nervous system depression, difficulty breathing

PHYSICAL HAZARDS: Flammable gas. May cause flash fire.

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: tearing, nausea, vomiting, symptoms of drunkenness, suffocation, convulsions, coma

LONG TERM EXPOSURE: no information on significant adverse effects

SKIN CONTACT:

SHORT TERM EXPOSURE: blisters, frostbite

LONG TERM EXPOSURE: no information is available

EYE CONTACT:

SHORT TERM EXPOSURE: frostbite, blurred vision

LONG TERM EXPOSURE: no information is available

INGESTION:

SHORT TERM EXPOSURE: frostbite

LONG TERM EXPOSURE: no information is available

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

SKIN CONTACT: If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

EYE CONTACT: Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

INGESTION: If a large amount is swallowed, get medical attention.

NOTE TO PHYSICIAN: For inhalation, consider oxygen.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Severe fire hazard. Vapor/air mixtures are explosive above flash point. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

EXTINGUISHING MEDIA: carbon dioxide, regular dry chemical

Large fires: Flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other

flammables. Evacuation radius: 800 meters (1/2 mile). Stop flow of gas.

FLASH POINT: -162 F (-108 C)

LOWER FLAMMABLE LIMIT: 2.0%

UPPER FLAMMABLE LIMIT: 11.1%

AUTOIGNITION: 851 F (455 C)

6. ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Avoid heat, flames, sparks and other sources of ignition. Do not touch spilled material. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

7. HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.110. Protect from physical damage. Store in a cool, dry place. Store in a well-ventilated area. Avoid heat, flames, sparks and other sources of ignition. Store outside or in a detached building. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

PROPYLENE:

ACGIH (simple asphyxiant)

VENTILATION: Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

CLOTHING: For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

GLOVES: Wear insulated gloves.

RESPIRATOR: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use.
For Unknown Concentrations or Immediately Dangerous to Life or Health -



Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.

Any self-contained breathing apparatus with a full facepiece.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: gas

COLOR: colorless

ODOR: Not available

MOLECULAR WEIGHT: 42.08

MOLECULAR FORMULA: C-H₃-C-H-C-H₂

BOILING POINT: -53 F (-47 C)

FREEZING POINT: -301 F (-185 C)

VAPOR PRESSURE: 7828 mmHg @ 21.1 C

VAPOR DENSITY (air=1): 1.5

SPECIFIC GRAVITY: Not applicable

DENSITY: 1.7855 g/L

WATER SOLUBILITY: 45%

PH: Not applicable

VOLATILITY: Not applicable

ODOR THRESHOLD: Not available

EVAPORATION RATE: Not applicable

VISCOSITY: 0.140 cP @ -40 C

COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable

SOLVENT SOLUBILITY:

Soluble: alcohol, ether, acetic acid

10. STABILITY AND REACTIVITY

REACTIVITY: May polymerize. May react on contact with air, heat, light or water.

CONDITIONS TO AVOID: Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

INCOMPATIBILITIES: oxidizing materials, halo carbons, halogens, acids

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: miscellaneous decomposition products

POLYMERIZATION: May polymerize. Avoid contact with heat, light, air, water or incompatible materials. Polymerizes with evolution of heat.

11. TOXICOLOGICAL INFORMATION

PROPYLENE:

CARCINOGEN STATUS: IARC: Human Inadequate Evidence, Animal Inadequate Evidence, Group 3;

ACGIH: A4 -Not Classifiable as a Human Carcinogen

TARGET ORGANS: central nervous system

TUMORIGENIC DATA: Available.

ADDITIONAL DATA: Stimulants such as epinephrine may induce ventricular fibrillation.

12. ECOLOGICAL INFORMATION

FATE AND TRANSPORT:

KOW: 223.87 (log = 2.35) (estimated from water solubility)

KOC: 533.33 (log = 2.73) (estimated from water solubility)

HENRY'S LAW CONSTANT: 9.6 E -4 atm-m³/mol

BIOCONCENTRATION: 0.40 (estimated from water solubility)

AQUATIC PROCESSES: 1.6862069 hours (River Model: 1 m deep, 1 m/s flow, 3 m/s wind)

ENVIRONMENTAL SUMMARY: Relatively non-persistent in the environment. Leaches through the soil or the sediment at a slow rate. Accumulates very little in the bodies of living organisms. Moderately volatile from water.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262.

Hazardous Waste Number(s): D001.

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

PROPER SHIPPING NAME: Propylene

ID NUMBER: UN1077

HAZARD CLASS OR DIVISION: 2.1

LABELING REQUIREMENTS: 2.1

QUANTITY LIMITATIONS:

PASSENGER AIRCRAFT OR RAILCAR: Forbidden

CARGO AIRCRAFT ONLY: 150 kg



CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

SHIPPING NAME: Propylene

UN NUMBER: UN1077

CLASS: 2.1

15. REGULATORY INFORMATION

U.S. REGULATIONS:

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Not regulated.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30): Not regulated.

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40): Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):

ACUTE: Yes

CHRONIC: No

FIRE: Yes

REACTIVE: No

SUDDEN RELEASE: Yes

SARA TITLE III SECTION 313 (40 CFR 372.65):

PROPYLENE

OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

STATE REGULATIONS:

California Proposition 65: Not regulated.

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION: A, B1.

NATIONAL INVENTORY STATUS:

U.S. INVENTORY (TSCA): Listed on inventory.

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CANADA INVENTORY (DSL/NDSL): Listed on inventory.

16. OTHER INFORMATION



**MATHESON
TRI•GAS**

ask. . .The Gas Professionals™

Page 7 of 7

©Copyright 1984-2005 MDL Information Systems, Inc. All rights reserved.

MATHESON TRI-GAS, INC. MAKES NO EXPRESS OR IMPLIED WARRANTIES, GUARANTEES OR REPRESENTATIONS REGARDING THE PRODUCT OR THE INFORMATION HEREIN, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR USE. MATHESON TRI-GAS, INC. SHALL NOT BE LIABLE FOR ANY PERSONAL INJURY, PROPERTY OR OTHER DAMAGES OF ANY NATURE, WHETHER COMPENSATORY, CONSEQUENTIAL, EXEMPLARY, OR OTHERWISE, RESULTING FROM ANY PUBLICATION, USE OR RELIANCE UPON THE INFORMATION HEREIN.